



**ARIA**  
BIOSAFETY CABINET



**ARIA**

## Dual Configuration MSC: Class II Microbiological Safety Cabinet and Cage Changing Station

Specifically designed for Animal Research Laboratories, Tecniplast ARIA Tech60 assures an effective barrier, prevents cross-contamination and allergen exposure. Simply typing a password, the operator can perform cage changing operations or microbiological activities (by adding the dedicated S/S working surface) in Class II Biohazard configuration.

### STANDARD FEATURES

- **Automated slanted sash window adjustable at two different heights** (250mm in biohazard configuration; 290 mm in cage changing procedure)
- **Electric auto lift system** (optional) for ergonomic positioning and easy transport
- **4.3" touch screen panel**
- **LED light bars with dimmer** (particularly beneficial for procedures with light-sensitive mice) and red LED lights to work at night (in CS mode)
- **Wide range of available options**

### PERFORMANCE

- **Lower energy costs, longer filter life, reduced noise, vibration and heat emissions** thanks to the EC high-performance and superior efficiency motor
- Sound-pressure levels (including alarms) way below the parameters of the current EN:12469
- TECH60 performances compliant with both the European and American standards of Class II Biosafety Cabinets

### BENEFITS

- **Outstanding flexibility and comfort** thanks to the extra wide working area
- **Bright and open working environment:** transparent glass side windows and LED light bars with dimmer
- No rounded corners: **easy to clean.** The AISI 304 (biohazard configuration) and the TRESPA (cage changing configuration) working surfaces are easily removable to perform routine cleaning and/or autoclaving sterilization procedures
- **Easy access to pre-filters** located in the rear of the panel, which preserves HEPA filters lifespan and efficiency
- **Noise and vibration minimization** thanks to the unique plenum design: acoustic comfort for both operators and animals



#### OVERALL DIMENSIONS (WxDxH)

1704 x 850 x 1998.5 - 2323.5 mm  
67"1/8 x 33"4/8 x 78"5/8 - 91"4/8 in

#### WORKING AREA DIMENSIONS (WxDxH)

1495 x 540 x avg 612 (flat mode) - 692 (recessed mode) mm  
58"7/8 x 21"2/8 x avg 24"1/8 (flat mode) - 27"2/8 (recessed mode) in

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =

COMPANY WITH  
ENVIRONMENTAL SYSTEM  
CERTIFIED BY DNV GL  
= ISO 14001 =

**TECNIPLAST**  
innovation through passion

#### HEADQUARTERS

ITALY | Tel. +39 0332 809711 · www.tecniplast.it · E-mail: tecnicom@tecniplast.it; venditeitalia@tecniplast.it  
SISTER COMPANIES

AUSTRALIA/NEW ZEALAND | Tel. + 61 2 8845 6500 · www.tecniplast.it · E-mail: info@tecniplast.com.au

CHINA | Tel. + 86 (0)21 50810920 · www.tecniplast.cn · E-mail: tecniplastchina@tecniplast.it

FRANCE | Tél. +33 (0)4 72 52 94 41 · www.tecniplast.fr · E-mail: info@tecniplast.fr

GERMANY | Tel. +49 (0)8805 921320 · www.tecniplast.de · E-mail: info@tecniplast.de

UNITED KINGDOM | Tel. + 44 (0)845 0504556 · www.tecniplastuk.com · E-mail: info@tecniplastuk.com

JAPAN | Tel. +81 (0)3 5770 5375 · www.tecniplast.it · E-mail: info@tecniplastjapan.co.jp

USA | Toll Free: +1 877.669.2243 · www.tecniplastusa.com · E-mail: info@tecniplastusa.com

CANADA | Toll Free: +1 855.347.8718 · www.tecniplastcanada.com · E-mail: info@tecniplastcanada.com

CAT175/ING - Rev Aug2017

Tecniplast reserves the right to change or modify product and/or specifications without notice or obligation.